



**Specifications Philips LED Waterproof Batten CoreLine WT120C 60W 8000lm - 840 Cool White | 150cm - Interact Dimmable - Through Wiring**

[View Product](#)

## General Information

|                          |                                    |
|--------------------------|------------------------------------|
| SKU                      | 249566                             |
| EAN                      | 8719514965362                      |
| manufacturer_code        | 8719514965362                      |
| Brand                    | Philips                            |
| Manufacturer Name        | WT120C G2 LED80S/840 WIA TW3 L1500 |
| Any Lamp all-in warranty | 5 Years                            |
| Average Lifetime (h)     | 50000                              |
| D-Mark                   | Yes                                |

## Technical Information

|                             |                                |
|-----------------------------|--------------------------------|
| Technology                  | LED Integrated                 |
| Replaces (Watt)             | 2x58                           |
| Wattage                     | 60W                            |
| Voltage (V)                 | 220-240                        |
| Dimmable                    | Dimmable with Philips Interact |
| Colour of Light             | White                          |
| Colour Code                 | 840 Cool White                 |
| Colour temperature (Kelvin) | 4000 Cool White                |
| Colour Rendering (Ra)       | 80-89                          |
| Light Colour Options        | Single Color                   |

|                       |                       |
|-----------------------|-----------------------|
| Luminous Flux (Lumen) | 8000lm                |
| Lumen per watt        | 133.3                 |
| Power factor          | >0.90                 |
| Length                | 150cm                 |
| Product Type Category | LED Waterproof Batten |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Surface                       |
| Fixture Connection     | PI [Push-in connector 5-pole] |
| Optical Cover          | PC (Polycarbonate)            |
| IP-Rating              | IP65                          |
| Impact Protection (IK) | IK08 - 5 joules               |
| Operating Temperature  | -20 to +35                    |
| Housing                | PC (Polycarbonate)            |
| Colour of the Fixture  | Grey                          |
| Colour of material     | Grey                          |
| Emergency Lighting     | No Emergency Unit             |
| Series                 | WT120C                        |

## Dimensions

|             |      |
|-------------|------|
| Length (mm) | 1515 |
| Width (mm)  | 80   |
| Height (mm) | 85   |

## Why Any-lamp?

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process